


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00090	Connector, dc plug, 6.5x3.0x24 mm, molding style	1	
2	30-00404	Wire, 2C TS, 24 AWG, UL2468, 300V, 80C, 3.0 mm, VW-1, PVC, 87A	1	
3	24-00258	Overmold, 6.5 plug, PVC	1	black



Notes:
Functionally equivalent components may be substituted

Wiring Diagram	
50-00090	wire color
center	black with stripe
sleeve	black

Revision:	Date:	Description:	Prepared: GL <small>Digitally signed by GL Date: 2018.02.08 14:14:38 -08'00"</small>	Notes: RoHS compliant Function test: no open, no short circuit, no intermittent	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	01/17/2018	Initial release	Verified: JP <small>Digitally signed by JP Date: 2018.02.13 13:30:35 -08'00"</small>	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 6.5x3.0x12 mm 50-00090 dc plug to 10 mm tinned, 24 AWG, UL2468, 30-00404 wire
					Size: A Part number: 10-02480
					Scale: 1:1 Sheet 1 of 1