



Tape is wound on a paper core.

The user must determine the suitability for use of the product for its intended use

ESD High Temp Masking Tape

Used in applications masking PCB gold features for wave soldering

- Waterproof
- Does tribocharge, but has minimal charge retention
- 7 mil (0.18 mm) total thickness
- Adhesive surface 1.2×10^{11} ohms
- Film resistance $< 1 \times 10^{11}$ ohms tested per ANSI/ESD S11.11 at 50% RH
- Max Temp 135°C (275°F) 45 minutes max
- Non-toxic, and pH neutral
- Non-corrosive
- Tensile: 22 lbs./in.
- Adhesion to Steel: 35 oz./inch²
- Elongation: 8%
- Temperature Range: -32°F to +275°F
- Adhesive Mass: Natural Rubber
- Adhesive: Non-Staining,
- Excellent Conformability
- Made in Canada

Note: Waterproof release coating does generate static charges during unrolling. We recommend slow unwinding, utilizing an Ionizer to neutralize charge.

Wescorp* Tape Storage and Limited Warranty:

The user must determine the suitability for use of an antistatic tape for his particular application. For best results, tape inventory should be continually replenished. It is recommended that rolls of tape be stored flat and rotated (flipped over to the other side) periodically. Tapes should be stored in a dry, well ventilated room with a reasonably consistent temperature of 68°F (20°C) and be protected from exposure to direct sunlight. Tape should not be stored in ultraviolet sunlight, moisture, or heat. Tape over one year old should be evaluated by the user to determine acceptability for the user's application. Protektive Pak recommends those tracking useful life of product to use shipping/invoice date as Protektive Pak expressly warrants that for a period of one (1) year from the date of purchase, our Wescorp Brand Antistatic Tape will be free of defects in material (parts) and workmanship (labor). See details of limited warranty online at <http://www.ProtectivePak.com/Warranty.aspx>.

*Wescorp is a Desco Industries brand.

Width - See Table

Width tolerance $\pm 1/32"$ (± 0.8 mm)

Tape	0.5" (13mm)	.75" (19mm)	1" (25mm)	Core	Length
ESD High Temp Masking	47020	47021	47022	3"(76mm)	60 yds

Tape widths are nominal metric ± 0.8 mm ($\pm 1/32"$).

- 1/2" is 12 mm nominal or 0.472"
- 3/4" is 18 mm nominal or 0.709"
- 1" is 24 mm nominal or 0.945"

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Protektive Pak Inc. letter on-line at ProtectivePak.com.

Specifications and procedures subject to change without notice.

WESCORP ESD HIGH TEMP MASKING TAPE, PAPER CORE

PROTEKTIVE PAK
13520 MONTE VISTA AVENUE, CHINO, CA 91710
PHONE (909) 627-2578, FAX (909) 363-7331
www.ProtectivePak.com

DRAWING NUMBER:
47020

DATE:
December
2011

PROTEKTIVE PAK