

469 SOLDERING STATION KIT – 60W



Key Features

- 60 Watt soldering iron
- Superior long-lasting PTC heating element
- Dual color LED to show temperature status
- Variable temperature control
- Integrated sponge cleaning tray with solder spool and iron holders
- Brass coil tip cleaner that fits in sponge tray area
- Desoldering pump and wick for removing solder
- 2oz spool of SRA 63/37 solder wire
- Fast Chip removal alloy and tacky flux sample for removing SMD components easily

Product Description

The 469 is a high performance soldering iron equipped with a fast-acting PTC ceramic heater suitable for beginner and advanced soldering. The separate tip and heater design offers easy replacement of tips. There are over 50 available tips to choose from.

**Uses standard type T-Series Aoyue tips.*

Package Contents

- Main Unit with Soldering Iron
- AOT-I Soldering Tip (Installed on iron)
- 469 Platform
- 469 Sponge Tray
- 469 Solder Spool Stand
- 469 Spring Iron Holder
- Instruction Manual

Kit Contents

- 63/37 .031" No Clean Solder Wire - 2oz Spool
- TY-98 Brass Coil Cleaner
- Rosin Solder Wick
- Aoyue Desoldering Pump
- Fast Chip TF5000 Tacky Flux
- 6.5" piece of Fast Chip Removal Alloy

Part Numbers for Re-order

Brass Coils Refill: AOREF98B

Solder Wire: WBNCC633731-2OZ

Fast Chip: SMDKIT



Specifications

Main Station

Input Voltage

AC 110V / 60 Hz

Temperature Scale

Analog 1 – 8

Station Dimensions

3.3 (L) x 2 (W) x 2.3" (H) (85 x 51 x 59mm)

Platform Dimensions

5.9 (L) x 4.3 (W) x 0.7" (H) (150 x 110 x 17mm)

Station Weight

1.17 Lbs (0.53 Kg)

Soldering Iron

Power Consumption

60W

Temperature Range

300 – 480°C (572 – 896°F)

Tip Type

T-Series

Soldering Iron Element

AOC011

