

# NS-205AF Series/NSM-205AF Series NEW

4-port 10/100 Mbps Ethernet with 1 Fiber Port Switch

# NS-206AF Series/NSM-206AF Series NEW

4-port 10/100 Mbps Ethernet with 2 Fiber Ports Switch

NS-205AFC-T/FCS-T/FCS-60T

NS-206AFT-T

NSM-205AFC-T/FCS-T/FCS-60T

NSM-206AFT-T



NS(M)-205AF/NS(M)-206AF Series

LAN <span style="color: red;">x 4</span>	Wide Temperature <span style="color: red;">-30 ~ +75</span>	DIN-Rail Mount	Wide Input Voltage <span style="color: red;">+12 ~ +48</span>	CE	FCC	RoHS	WEEE	For NS(M)-205AF 100Base-FX <span style="color: red;">x 1</span>	For NS(M)-206AF 100Base-FX <span style="color: red;">x 2</span>
--	---	----------------	---	----	-----	------	------	---	---

## Features ▶▶▶

- Provides 1 x 100-FX fiber port for NS-205AF/NSM-205AF series
- Provides 2 x 100-FX fiber ports for NS-206AF/NSM-206AF series
- Full duplex IEEE 802.3x and half duplex backpressure flow control
- Supports operating temperatures from -30 °C ~ +75 °C
- Automatic MDI/MDI-X crossover for plug-and-play
- Store-and-forward architecture
- Redundant dual +12 V<sub>DC</sub> ~ +48 V<sub>DC</sub> power inputs
- DIN-Rail Mounting

## Introduction

The NS-206AF/NSM-206AF is a 4-port unmanaged Ethernet with 2 fiber ports switch. Using fiber optics, you can prevent noise from interfering with your system and supports high-speed (100 Mbps) and high-distance (up to 60 km) transmissions.

The NS-205AF/NSM-205AF/NS-206AF/NSM-206AF provides a wide +12 V<sub>DC</sub> ~ +48 V<sub>DC</sub> power range to fit all the common power standards found in industrial automation, without external power converters. The wide power input lowers installation and maintenance costs.

## Comparison Table of Fiber Switch

Mode Name	NS-205F NS-206F	NSM-205F NSM-206F	NS-205AF NS-206AF	NSM-205AF NSM-206AF
PoE	-			
Input Voltage Range	+10 V <sub>DC</sub> ~ +30 V <sub>DC</sub>		+12 V <sub>DC</sub> ~ +48 V <sub>DC</sub>	
Operating Temperature	0 °C ~ +70 °C		-30 °C ~ +75 °C	
Casing	Plastic	Metal (IP20)	Plastic	Metal (IP30)
Installation	DIN-Rail Mounting	DIN-Rail Mounting or Wall Mounting	DIN-Rail Mounting	
Dimensions (W x L x H) (Unit: mm)	64 x 98 x 110	73 x 102 x 110	31 x 127 x 157	25 x 133 x 168


**Specifications**

Models	NS-205AF Series	NS-206AF Series	NSM-205AF Series	NSM-206AF Series
<b>Technology</b>				
Standards	IEEE 802.3, 802.3u, 802.3x			
Processing Type	Store & forward; wire speed switching			
MAC Addresses	1024			
Memory Bandwidth	2.0 Gbps			
Frame Buffer Memory	512 Kbit			
Flow Control	IEEE 802.3x flow control			
<b>Ethernet Interface</b>				
RJ-45 Ports	10/100 Base-T(X) auto negotiation speed, F/H duplex mode, and auto MDI/MDI-X connection			
LED Indicators	Power, Link/Act, 10/100M			
Ethernet Isolation	1500 V <sub>rms</sub> 1 minute			
+/-4 kV ESD Protection	Yes			
<b>Fiber Interface (100 Base-FX; SC/ST type)</b>				
Multi-Mode	NS-205AFT-T NS-205AFC-T NSM-205AFT-T NSM-205AFC-T NS-206AFT-T NS-206AFC-T NSM-206AFT-T NSM-206AFC-T	Multi mode fiber cables: 50/125, 62.5/125 or 100/140 $\mu$ m Distance: 2 km, (62.5/125 $\mu$ m recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -20 dBm Max. TX Output: -14 dBm Max. RX Sensitivity: -32 dBm Min. RX Overload: -8 dBm Budget: 12 dBm		
Single-Mode	NS-205AFCS-T NSM-205AFCS-T NS-206AFCS-T NSM-206AFCS-T	Single-mode fiber cables: 8.3/125, 8.7/125, 9/125 or 10/125 $\mu$ m Distance: 30 km, (9/125 $\mu$ m recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -15 dBm Max. TX Output: -8 dBm Max. RX Sensitivity: -34 dBm Min. RX Overload: -5 dBm Budget: 19 dBm		
Single-Mode	NS-205AFCS-60T NSM-205AFCS-60T NS-206AFCS-60T NSM-206AFCS-60T	Single-mode fiber cables: 8.3/125, 8.7/125, 9/125 or 10/125 $\mu$ m Distance: 60 km, (9/125 $\mu$ m recommended) for full duplex Wavelength: 1300 or 1310 nm Min. TX Output: -5 dBm Max. TX Output: 0 dBm Max. RX Sensitivity: -35 dBm Min. RX Overload: -5 dBm Budget: 30 dBm		
<b>Power Input</b>				
Input Voltage Range	+12 V <sub>dc</sub> ~ +48 V <sub>dc</sub> (Redundant input)			
Power Consumption	0.2 A @ 24 V <sub>dc</sub>	0.14 A @ 24 V <sub>dc</sub>	0.2 A @ 24 V <sub>dc</sub>	0.14 A @ 24 V <sub>dc</sub>
Protection	Power reverse polarity protection			
+/-4 kV ESD Protection	Yes			
Connector	6-Pin Removable Terminal Block			
<b>Mechanical</b>				
Casing	Plastic (Flammability UL 94V-0)		Metal (IP30 Protection)	
Dimensions (W x L x H)	31 mm x 127 mm x 157 mm		25 mm x 133 mm x 168 mm	
Installation	DIN-Rail Mounting			
<b>Environmental</b>				
Operating Temperature	-30 °C ~ +75 °C			
Storage Temperature	-40 °C ~ +85 °C			
Ambient Relative Humidity	10% ~ 90% RH, non-condensing			