



Drawings not to scale

Rectangular Flashing Safety Light - 40° Tilt Activated, Fully Sealed

Part Number: RBM-40 **Product Data Sheet** 

## **PICTURE ACTIVATION DIMENSIONS** 900 50.0 21.0 (0.826) 180 $\bigcirc$ 70.0 (2.755) 2 x Ø 6.60 (0.259) THRU ALL Ø 14.55 (0.572) CE F©

SPECIFICATION		
Activation Angle	Degree	220° - 20°
Battery Life		Up to 5 years (under normal conditions)
Number of LED'S		8 total - 4 per side
Operating Temperature	Celcius	-20° to 85° (-50°min, flash rate increased & lifetime reduced)
Flash Rate	Pulse/min	60 at 20°
Battery Voltage (non replaceable)	Volts	3.6
Fixing Holes		2 x 6.6mm (50mm centres)
IP Rating		68
Material		Resin filled Polycarbonate Shell

Reccomended Mounting position

## **Applications Include**

- Tail Lift / Ramp Safety Warning.
- Lorry Outrigger indication.
- Fork Lift Safety Warning.
- Hazardous Obstruction Warning.

## **Options**

- Colour: Standard Amber
- Other colours available, please enquire.
- Customer specific activation angle and pulse rate.
- Number of LEDS / grouped led angles.
- If you do not see what you need, jusk ask, as there is a strong possibility we can do it!

## Did you know we also sell?

















Rev. No. **Revision Note Date Signature** 0 22-11-12 ML Data sheet



As part of the company policy of continued product improvement, specifications may change without notice. Our sales office will be pleased to help you with the latest information on this product range and the details of our full design and manufacturing service. All products are supplied to our standard conditions of sale unless otherwise agreed in writing.

Phone: +44 (0)1255 862236 www.comuseurope.co.uk Fax: +44 (0)1255 862014