




Items	Content Revised	Date
1		



Technical requirements:

1. Plug: a: UE-333, Current (A) : 20, Voltage (V) : 250
b: UE-334, Current (A) : 20, Voltage (V) : 250
2. Cord: Soft SJT #12/3C 105°C
3. High Voltage Tested: 1500V/S No Attacked, No Flicker
4. No nick, Spot, Mottle Nn Appearance and Wording is Clearly
5. The All Material Compliance with RoHS and REACH



CORD MARKING: E176096 (UL) SJT VW-1 105°C 300V 3x3.31mm² (12AWG)
Or C(UL) SJT FT1 105°C 300V 3x3.31mm² (12AWG) UNIRISE

BOM表

8	LK0713	PE two side strip13CM	1PCS
7	-----	SJT 12/3C 105°C Soft	1PCS
6	-----	UE-334 Inner frame	1PCS
5	-----	Earth Blade of UE-334	1PCS
4	-----	L and N Blade of UE-334	2PCS
3	BK116000	PVC of plug 77A	/
2	-----	UE-333 Inner frame	1PCS
1	-----	Blade of UE-333	3PCS
Items	Part Number	Description	Q' TY

CUSTOMER CONFIRM	Colors available: Black, Blue, Red, Green, Yellow, Orange, White	
Drawing No.		Page: Version: A
Power Supply Cord: UE-333+UE-334		Approved by:
Customer:		Checked by:
		Drawn by:
	Unit: mm	Sheet: $\frac{1}{1}$
		DATE: 2013-01-23