




Connectors System AC 164 Plug and Socket Connectors Tall Version

AC 164 BU/ 3 WS

socket, 3 pole, white, coding: 1 (mains), voltage rating: 250 V, current rating: 16 A, cross-section rating: 2.5 mm²



Order Info

reference number (ref.no.)	147053
PU	200
EAN	4028012122288

Type

type	socket
number of poles	3 pole
clamping units per pole	1
colour	white
coding	1 (mains)
cross-section rating	2.5 mm ²
PE function	yes
protection against incorrect plugging	yes
latch	yes

Technical Data

voltage rating	250 V
current rating	16 A
impulse voltage rating	4.0 kV
contact material	brass
core cross-section min.	0.5 mm ²
core cross-section max.	2.5 mm ²
flammability rating	V-2
max. ambient temperature operation	70 °C
IP code	IP20
IP code when plugged	IP40
type of conductor solid	yes
type of conductor flexible	yes
type of conductor stranded	yes
stripping length	7.0 mm
assembly contact screw	PZ 1 / ⚙ 0,5 Nm

Approvals

acc. to EN 61535	Download PDF
-------------------------	------------------------------

acc. to UL	Download PDF
-------------------	------------------------------

Accessories

AC 164 BC/ 3 SW	149563
------------------------	--------

AC 164 BC/ 3 WS	149553
------------------------	--------
