

## TECHNICAL DATA SHEET

Part#: 7375E

**Cutters - 50°Angulated Head - Blade Length .125"**

Offers excellent visibility and accessibility with our smallest angulated (.16") blade

The 7375E Lazer Line<sup>®</sup> sub-miniature angulated/tapered optimum flush cutter with a cutting capacity of .001" - .010" soft wire. It is made of carbon tool steel with induction hardened cutting blades to RHC 63-65. This 4.25" tool has a 40°angled/tapered head. The set-screw prevents over-travel while prolonging the life of the tool. It features a ergonomically molded antimicrobial Anti-Static grip (10<sup>10</sup> ohms/sq surface resistivity) with dual leaf springs.

• Precision Level	★★★★★
• Material	Carbon
• Surface Resistivity	10 <sup>10</sup> ohms/sq
• Shape	Angulated Head
• Type of Cut	Lazer Flush
• Cutting Capacity	.001 - .010"
• Blade Angle	50°
• Blade Length	.125"
• Body Width	0.32" (8mm)
• Body Height	
• OAL	4.25" (106.25mm)
• Weight (OZ)	3
• UPC	662847013393
• Schedule B	8203.20.60.60
• ECCN	EAR99
• UNSPSC Code	27111511
• Country of Origin	USA
• Group	Angled Head

